

## LIFT POSITION INDICATOR





## PI-43s LIFT POSI

LANDSCAPE MOUNTING

LIFT POSITION INDICATOR

PORTRAIT MOUNTING

**B2** 

The Pi-43s offers all the essential elevator display information in full colour. Designed to be compact fitting into tight fixtures and COP's, with its high viewing angles, allowing both landscape or portrait mounting. Ideal for landing installs or the essential elevator colour display this screen is full of features, allowing complete programmable functions with intelligent gong and hall lantern outputs to trigger external devices. The display can be connected directly to both Pixel and KONE SPi data bus.

## SPECIFICATIONS

- Screen size : 4.3"
- LCD Display Type : 16-bit Colour LCD
- Resolution (Pixels) : 480x272 / 16:9
- Viewing Area (wxh) (mm) : 55 x 97
- Power Supply : 12-30V DC (60mA @ 24V DC)
- GONG/Hall Lantern Output : +24VDC, 350mA(max)
- Dimensions (wxhxd) (mm) : 127 x 68.5 x 19.5
- Lift Interface : Pixel & DCT Mode 2,3 / KONE SPI
- Programming Interface : RS-232/RS485





## FEATURES

Standard Inclusions: 4.3" 16 bit colour Display Wide viewing angle Low power consumption Landscape and Portrait mounting Direction, floor and lift status message indication Background image or solid colour Auto sleep mode Chime & Lantern output drive Direct KONE SPI with built in messages for Plug n Play Pixel Technologies serial DataBus protocol Supports up to 127 floor levels Programmable via Windows software





+61 3 8843 0700



www.pixeltechnologies.com.au info@pixeltechnologies.com.au



Melbourne | Sydney Brisbane | Singapore | Christchurch

> © 2023 Pixel Technologies Pty Ltd Supplier No. E5405

Proudly Designed & Manufactured in Australia for the World

Pixel Technologies assumes no responsibility for any errors that may appear in this publication. All images are for illustration purposes only. Specifications are subject to change without prior notice.

All information stated in the brochure is correct at time of printing and subject to change without notice.